

PS-3019A 19" CCTV Monitör



Product Feature

- Resolution input: 1920x1080@60Hz
- Multi-channel signals input, with stereo speaker
- Adopt the newest LCD blue ray technology, 3D digital comb filtering and 3D noise reduction technology.
- Color 16.7M (8-bit), image natural and exquisite.
- 5ms response time, no delaying.
- External power adapter, low consumption, service life above 60,000 hours.
- Adopt adaptive power supply, meet variable countries requirement.
- Use ABS plastic body, desktop base included.

	Model	PS-3019A
Panel Specification	Panel size:	19" TFT LCD
	Resolution:	1920x1080
	Aspect ratio:	16:10
	Brightness (cd/m ²):	260(typ)
	Refresh rate:	60 Hz
	Contrast ratio:	4000:1
	Visual angle:	178°/178°
	Response time:	5ms
	Color:	16.7M(8-bit)
Input Interface	USB input:	USB×1
	HDMI input:	HDMI×1
	RCA input:	RCAx3
	VGA	VGAx1
VESA	Wall mounting hole size:	75x75mm
Audio	Audio in/out	Yes
Operating Environment	Working temperature:	0°C~50°C
	Storage temperature	-20°C~60°C
	Working humidity	5%~90%
Power Consumption	Power supply	AC180V-240V ≤18W
	Standby consumption	≤1W
Package	Dimension(mm)	485(W)x340(H)x105(D); 5PCS/CTN: 550(W)x370(H)x500(D)
	Gross weight(kg)	3.5kg; 18kg
	Accessory include	1*power adapter, 1* HDMI cable, 1*quick guide, 1* desktop bracket
Industry Standards	Quality standard	Passed RoHS FCC CE China 3C China Energy Saving Patent certificate Patent Right
	Installation method	Desktop base, wall mount
	Housing material	ABS plastic
	Housing color	Black
OSD	Menu language	Support English, Spanish, Turkish, Russian...more than 20 languages