

### PS-3200A

### 32" CCTV Monitor



## Product Feature

- Resolution: 1920x1080.
- Multi-channel signals input, with stereo speaker
- Adopt the newest LCD blue ray technology, 3D digital comb filtering and 3D noise reduction technology.
- Color 16.7M (8-bit), image natural and exquisite.
- 6ms response time, no delaying.
- Internal power supply with low consumption, service life above 60,000 hours.
- Adopt adaptive power supply, meet variable countries requirement.
- Use ABS plastic body, desktop base included.

	Model	PS-3200A
<b>Panel Specification</b>	Panel size:	32" TFT LCD
	Resolution:	1920x1080@60hz
	Aspect ratio:	16:9
	Brightness (cd/m <sup>2</sup> ):	280(typ)
	Refresh rate:	60Hz
	Contrast ratio:	3000:1
	Visual angle:	178°/178°
	Response time:	6ms
	Color:	16.7M(8-bit)
<b>Input Interface</b>	USB input:	USB×2
	HDMI input:	HDMI×2
	RCA input:	RCAx3
	VGA	VGAx1
<b>VESA</b>	Wall mounting hole size:	200x150mm
<b>Audio</b>	Audio in/out	Yes
<b>Operating Environment</b>	Working temperature:	0°C~50°C
	Storage temperature	-20°C~60°C
	Working humidity	5%~90%
<b>Power Consumption</b>	Power supply	AC100V-240V, 35W
	Standby consumption	≤3W
<b>Package</b>	Dimension(mm)	820(W)x540(H)x138(D)mm; 2PCS/CTN: 845(W)x565(H)x300(D)mm
	Gross weight(kg)	4.7kg 1pcs; 10.65kg 2pcs
	Accessory include	1*power cable, 1* HDMI cable, 1*quick guide, 1* desktop bracket
<b>Industry Standards</b>	Quality standard	Passed RoHS  FCC  CE   China 3C  China Energy Saving Patent certificate   Patent Right
	Installation method	Desktop base, wall mount
	Housing material	ABS plastic
	Housing color	Black
<b>OSD</b>	Menu language	Support English, Spanish, Turkish, Russian...more than 20 languages