

S1500-P Series

Overview

BDCOM S1500-P Series is a multi-functional unmanaged full-gigabit PoE switch with large buffer capacity. The product is primarily applied in access layer of CCTV and WLAN. BDCOM S1500-P Series PoE switches include twelve models: S1500-4P2S, S1500-4P2G, S1500-4P1G1S, S1500-8P2S, S1500-8P2G, S1500-8P2G2S, S1500-16P2S, S1500-16P2G2S, S1500-24P2S, S1500-24P2S-370, S1500-16P2ES-H, S1500-24P2ES-H, catering to the needs of different-scale deployments in multiple industries such as finance, education, hospitality, healthcare, transportation, energy and manufacturing, empowering the establishment of simplified and secured network.



Highlights

Switching Features

- Non-blocking switching architecture, and line-speed forwarding of all ports
- Large buffer design, ensures smooth playback of high-definition videos
- Supports IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control
- Multi-functional DIP modes to meet various networking requirements

Practicability

- Plug and play
- LED indicators to show working status

CCTV-Mate

PoE Features

- Compliant with IEEE802.3af/at/bt standards, with a maximum PoE power of 60W output
- High-power PoE power supply, supporting full load 802.3af on all ports
- Intelligent standard 48V PoE, negotiating power supply based on terminal type
- Supports short-circuit protection and overcurrent protection

Reliability

- Integrated professional lightning protection circuit, with high-level lightning protection
- Built-in high-quality PoE power supply, ensuring safe and stable PoE output
- Compliant with CE and FCC safety standards

Model

S1500-4P2S



- 4-Port Gigabit PoE+ 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 3 to 4 port extension
 - VLAN – 1 to 4 port isolation
- Dimensions (WxDxH): 200x118x44mm

S1500-4P2G



- 4-Port Gigabit PoE+ 2-Port Gigabit RJ45
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 3 to 4 port extension
 - VLAN – 1 to 4 port isolation
- Dimensions (WxDxH): 200x118x44mm

S1500-4P1G1S



- 4-Port Gigabit PoE+ 1-Port Gigabit RJ45 + 1-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 3 to 4 port extension
 - VLAN – 1 to 4 port isolation
- Dimensions (WxDxH): 200x118x44mm

S1500-8P2S



- 8-Port Gigabit PoE+ 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 7 to 8 port extension
- Dimensions (WxDxH): 200x161x44mm

S1500-8P2G



- 8-Port Gigabit PoE+ 2-Port Gigabit RJ45
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 7 to 8 port extension
 - VLAN – 1 to 8 port isolation
- Dimensions (WxDxH): 200x118x44mm

S1500-8P2G2S



- 8-Port Gigabit PoE+ 2-Port Gigabit RJ45 + 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 7 to 8 port extension
- Dimensions (WxDxH): 200x161x44mm

Model

S1500-16P2S



- 16-Port Gigabit PoE+ 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 9 to 16 port extension
 - VLAN – 1 to 16 port isolation
- Dimensions (WxDxH): 440x204x44mm

S1500-16P2G2S



- 16-Port Gigabit PoE+ 2-Port Gigabit RJ45 + 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode: Default - Standard operating mode
- CCTV – 9 to 16 port extension VLAN – 1 to 16 port isolation
- Dimensions (WxDxH): 440x204x44mm

S1500-24P2S



- 24-Port Gigabit PoE+ 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 17 to 24 port extension
 - VLAN – 1 to 24 port isolation
- Dimensions (WxDxH): 440x204x44mm

S1500-24P2S-370



- 24-Port Gigabit PoE+ 2-Port Gigabit SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 17 to 24 port extension
 - VLAN – 1 to 24 port isolation
- Dimensions (WxDxH): 440x280x44mm

S1500-16P2ES-H



- 2-Port Gigabit PoE++ 14-Port Gigabit PoE+ 2-Port 2.5G SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 9 to 16 port extension
 - VLAN – 1 to 14 port isolation
- Dimensions (WxDxH): 440x204x44mm

S1500-24P2ES-H



- 2-Port Gigabit PoE++ 22-Port Gigabit PoE+ 2-Port 2.5G SFP
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 17 to 24 port extension
 - VLAN – 1 to 22 port isolation
- Dimensions (WxDxH): 440x204x44mm

Specifications

Item	S1500-4P2S	S1500-4P2G	S1500-4P1G1S	
Switching capacity	12Gbps	12Gbps	12Gbps	
MAC	2K	2K	2K	
Buffer size	448Kb	448Kb	448Kb	
PoE Port	4 Gigabit	4 Gigabit	4 Gigabit	
Uplink RJ45	/	2 Gigabit	1 Gigabit	
Uplink SFP	2 Gigabit	/	1 Gigabit	
Dimensions (mm)	200x118x44	200x118x44	200x118x44	
PoE budget	≤60W	≤60W	≤60W	
Item	S1500- 8P2S	S1500-8P2G	S1500-8P2G2S	
Switching capacity	20Gbps	20Gbps	24Gbps	
MAC	2K	2K	2K	
Buffer size	448Kb	448Kb	448kb	
PoE Port	8 Gigabit	8 Gigabit	8 Gigabit	
Uplink RJ45	/	2 Gigabit	2 Gigabit	
Uplink SFP	2 Gigabit	/	2 Gigabit	
Dimensions (mm)	220x161x44	220x161x44	220x161x44	
PoE budget	≤90W	≤90W	≤90W	
Item	S1500-16P2S	S1500-16P2G2S	S1500-24P2S	S1500-24P2S-370
Switching capacity	36Gbps	40Gbps	52Gbps	52Gbps
MAC	8K	8K	8K	8K
Buffer size	4Mb	4Mb	4Mb	4Mb
PoE Port	16 Gigabit	16 Gigabit	24 Gigabit	24 Gigabit
Uplink RJ45	/	2 Gigabit	/	/
Uplink SFP	2 Gigabit	2 Gigabit	2 Gigabit	2 Gigabit
Dimensions (mm)	440x204x44	440x204x44	440x204x44	440x280x44
PoE budget	≤180W	≤185W	≤280W	≤370W
PoE standard	802.3af/at, maximum output of 30W per port			
Power supply	Built-in AC: 100-240V, 50/60Hz			
Working mode	VLAN mode, Default mode, CCTV mode			
Environment requirements	Operating temperature/humidity:0°C-50°C, 10%-90% non-condensing Storage temperature/humidity: -40°C-70°C, 5%-95% non-condensing			
Fan	Fanless			
Lightning protection	4KV			

Specifications

Item	S1500-16P2ES-H	S1500-24P2ES-H
Switching capacity	42Gbps	58Gbps
MAC	16K	16K
Buffer size	8.4Mbit	8.4Mbit
Gigabit PoE port	PoE++	2(60W)
	PoE+	14(30W)
		22(30W)
Uplink SFP	2-Port 2.5G	2-Port 2.5G
Dimensions (mm)	440x204x44	440x204x44
PoE budget	≤180W	≤260W
Power supply	Built-in AC: 100~240V, 50/60Hz	
Working mode	VLAN mode, Default mode, CCTV mode	
Environment requirements	Operating temperature/humidity:0°C-50°C, 10%-90% non-condensing Storage temperature/humidity: -40°C-70°C, 5%-95% non-condensing	
Fan	Fanless	
Lightning protection	4KV	

Ordering Information

S1500-4P2S	4-Port Gigabit PoE+ 2-Port Gigabit uplink SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 60W, desktop/rack-mounted installation
S1500-4P2G	4-Port Gigabit PoE+ 2-Port Gigabit uplink RJ45 Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 60W, desktop/rack-mounted installation
S1500-4P1G1S	4-Port Gigabit PoE+ 1-Port Gigabit uplink RJ45 + 1-Port Gigabit uplink SFP Unmanaged PoE Switch,DIP function, built-in AC220V power supply; PoE budget 60W, desktop/rack-mounted installation
S1500-8P2S	8-Port Gigabit PoE+ 2-Port Gigabit uplink SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 90W, desktop/rack-mounted installation
S1500-8P2G	8-Port Gigabit PoE+ 2-Port Gigabit uplink RJ45 Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 90W, desktop/rack-mounted installation
S1500-8P2G2S	8-Port Gigabit PoE+ 2-Port Gigabit uplink RJ45 + 2-Port Gigabit uplink SFP Unmanaged PoE Switch,DIP function, built-in AC220V power supply; PoE budget 90W, desktop/rack-mounted installation
S1500-16P2S	16-Port Gigabit PoE+ 2-Port Gigabit uplink SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 180W, desktop/rack-mounted installation
S1500-16P2G2S	16-port GE PoE+ 2-port GE RJ45 + 2-port GE SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; 185W PoE budget, desktop/rack-mounted installation
S1500-24P2S	24-Port Gigabit PoE+ 2-Port Gigabit uplink SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 280W, rack-mounted installation
S1500-24P2S-370	24-Port Gigabit PoE+ 2-Port Gigabit uplink SFP Unmanaged PoE Switch, DIP function, built-in AC220V power supply; PoE budget 370W, rack-mounted installation
S1500-16P2ES-H	2-Port Gigabit PoE++ 14-Port Gigabit PoE+ 2-Port 2.5G SFP Unmanaged PoE Switch, built-in AC-220V power supply; 180W PoE budget, desktop/rack-mounted installation
S1500-24P2ES-H	2-Port Gigabit PoE++ 22-port Gigabit PoE+ 2-port 2.5G SFP Unmanaged PoE Switch, built-in AC-220V power supply; 260W PoE budget, desktop/rack-mounted installation

Copyright © Shanghai Baud Data Communication Co., LTD.2025. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.

