

PS-5500A-4K 55" CCTV Monitör



Product Feature

- Resolution: UHD 3840x2160 (4K@60hz)
- Multi-channel signals input, with stereo speaker
- Adopt the newest LCD blue ray technology, 3D digital comb filtering and 3D noise reduction technology.
- Color 16.7M (8-bit), image natural and exquisite.
- 6ms response time, no delaying.
- Internal power supply with low consumption, service life above 60,000 hours.
- Adopt adaptive power supply, meet variable countries requirement.
- Use ABS plastic body, desktop base included.

Model		PS-5500A-4K
Panel Specification	Panel size:	55" TFT LCD
	Resolution:	3840X2160 (4K@60hz)
	Aspect ratio:	16:9
	Brightness (cd/m²):	300(typ)
	Refresh rate:	60Hz
	Contrast ratio:	1200:1
	Visual angle:	178°/178°
	Response time:	6ms
	Color:	16.7M(8-bit)
	USB input:	USB×1
	HDMI input:	HDMI×2
	DVI	DVIX1
	VGA	VGAx1
	BNC	BNCX1
VESA	Wall mounting hole size:	200x200mm
Audio	Audio	Built- in speaker
	Audio in/out	Yes
Operating Environment	Working temperature:	0℃~50℃
	Storage temperature	-20℃~60℃
	Working humidity	5%~90%
Power Consumption	Power supply	AC100V-240V, 90W
	Standby consumption	≤1W
Package	Dimension(mm)	1330(W)x840(H)x160(D)mm; 2PCS/CTN: 1355(W)x870(H)x335(D)mm
	Gross weight(kg)	12.7kg 1pcs; 28.55kg 2pcs
	Accessory include	1*power cable, 1* HDMI cable, 1*quick guide, 1* desktop bracket
Industry Standards	Quality standard	Passed RoHS FCC CE China 3C China Energy Saving Patent certificate Patent Right
	Installation method	Desktop base, wall mount
	Housing material	ABS plastic
	Housing color	Black
OSD	Menu language	Support English, Spanish, Turkish, Russian...more than 20 languages